

# miniRaman Spectrometer

The world's smallest Raman Spectrometer



- Premium performance for quantitative analysis
- Excellent for material identification
- Accurate with high sensitivity
- Extended spectral range via dual laser
- Affordable

#### **Miraspec**

#### Software for PC (Windows 10, 11) and smartphone (Android)

Data acquisition	Laser power control		
	Exposure time control		
	Sensor gain control		
	Number of repetitions control		
	Spectral range control		
Data preprocessing options	<ul> <li>Spike correction         <ul> <li>(Whitaker-Hayes, moving window)</li> </ul> </li> <li>Spectral smoothing         <ul> <li>(Whittaker, asymmetric least squares, Savitzky-Golay)</li> </ul> </li> <li>Baseline correction         <ul> <li>(rolling circle, rubberband, least squares, asymmetrically reweighted penalized)</li> </ul> </li> <li>Spectrum normalization         <ul> <li>(Z-score, mean, Mean centre, MinMax, Unit Norm L1, Unit Norm L2)</li> </ul> </li> <li>Intensity normalization*     </li> </ul>		
	Laser mode-hop correction*		
	Spectral super resolution*		
Data	Principal component analysis		
Exploration	Non-negative matrix factorization (SIMPLISMA-NNLS, MCR-ALS)		
Qualitative analysis	Material identification (Pearson correlation, square Euclidean cosine, square first difference Euclidean cosine) Compatible libraries		
	(>20,000 spectra)**		
	Creation of spectral libraries		
Quantitative analysis	Principal component regression		
	Raman peak height/peak area calibration		
	Partial Least Squares (PLS) calibration		
Classification	Random Forest, Linear SVM, AdaBoost, Decision Tree, Hoefding Tree, Naïve Bayes, Perceptron, Softmax Regression		

\*patented feature \*\*various library options available upon request

System controlled by smartphone or PC via Bluetooth or USB-C cable.



### **Accessories**

- Short/ Middle • working distance probe, f=15 mm
- Long working distance probe, f=30 mm
- Contact probe •
- Disposable silicone . heads
- Sample/Vial • holders
- Axial focusing accessories
- Light protection sample cover
- Power bank •
- Belt Holder •
- Docking station •

### **Applications**

#### For researchers, industries, universities and general consumers



Life Sciences & Health: Biosciences, pharmaceuticals, skin diagnostics, cosmetics



#### Materials & Nanotechnology: Polymers, nano-materials, semiconductors, surface enhanced Raman scattering (SERS)



**Industrial & Chemical Analysis:** Chemicals, geology, forensics



**Quality Control & Authentication:** Alcohol quality, counterfeit product detection



#### **Unique Technology**



The **miniRaman Spectrometer** is an innovative, miniaturized Raman spectrometer equipped with a patented, integrated **reference channel**. This innovative technology ensures **automatic calibration** by correcting for laser wavelength drift. The system continuously adjusts the Raman shift and intensity of the sample spectrum, delivering fast, accurate, and reliable results. These advanced features make the miniRaman spectrometer an ideal solution for **material identification** and precise quantitative measurements.

### Specification

Feature versus model	miniRaman Standard	miniRaman SERS	miniRaman Dual	miniRaman Full Range
Laser wavelength	785 nm		660 nm and 785 nm	660 nm
Power on Sample*	5-50 mW	0.5-15 mW	5-35 mW (660) 5-50 mW (785)	10-80 mW
Spectral Range	270-30	00 cm <sup>-1</sup>	2700-3900 cm <sup>-1</sup> (660) 300-2700 cm <sup>-1</sup> (785)	270-3900 cm <sup>-1</sup>
Spectral Resolution**	8,10,1	4 cm <sup>-1</sup>	12,16,20 cm <sup>-1</sup> (660) 8,10,14 cm <sup>-1</sup> (785)	12,16,20 cm <sup>.1</sup>
Signal-to-noise ratio***	500:1	100:1	800:1 (660) 440:1 (785)	800:1

\* Actual laser power range can differ ± 2 % per device. Please contact us if you need specific laser power range values

\*\* Slit size dependent; slit size can be customized (20, 35, 50 um slits)

\*\*\* Determined as peak signal-to-noise ratio of polystyrene spectrum at maximal laser power, integration time 0.3s, number of repetitions 10.

## **Extra Features**

- Small size (105 x 50 x 45 mm)
- Lightweight (360 g)
- One button operation
- Low power consumption (Up to 4 hr)
- Bluetooth & USB connectivity

## Customisation

Operator body - IP67 and Drop resistant body design



# Contact Details

Lightnovo ApS Blokken 11, 1. 3460 Birkerød Denmark (DK) +45 71 37 04 10 info@lightnovo.com

CVR: 40979603

# **About Lightnovo**

A spin-off from the Technical University of Denmark, Lightnovo was founded in 2019 by an enthusiastic team united by the goal of revolutionizing the field of Raman spectroscopy through innovative, high-performance solutions. Our mission is to develop and commercialize "Raman for all: democratize the power of high-end Raman spectroscopy for the benefit of mankind".

We aim to provide premium performance Raman spectrometers and microscopes with the world's smallest form factors without compromising the performance. With this innovation, Lightnovo addresses the need for portable, reliable field instruments at an affordable price. © 2025 Lightnovo Aps. All rights reserved

Scan to learn more about this and other products





Please consult your local sales representative for details