Lightnovo mini Raman spectrometer 2026

mRs Lab body

Name	Laser power on sample	Spectral slit sizes	Signal-to-noise ratio*	Spectral Range	Raman shift	Spectral resolution	Grating	Physical dimensions	Weight
mRs 660 Full Range Power	10-80mW	20, 35, 50µm	500:1	679 - 882nm	270 - 3700cm-1	0.36nm/px, 9-13cm-1 / 11-15cm-1 / 13-17cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	105x50x45 (LxWxH)	360g
mRs 660 Full Range SERS	1-15mW	20, 35, 50µm	100:1	679 - 882nm	270 - 3700cm-1	0.36nm/px, 9-13cm-1 / 11-15cm-1 / 13-17cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	105x50x45 (LxWxH)	360g
mRs 785 Standard	5-50mW	20, 35, 50µm	500:1	808-982nm	300 - 3200cm-1	0.25nm/px, 6-9cm-1 / 7-10cm-1 / 9-13cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	105x50x45 (LxWxH)	360g
mRs 785 SERS	1-15mW	20, 35, 50µm	100:1	808-982nm	300 - 3200cm-1	0.25nm/px, 6-9cm-1 / 7-10cm-1 / 9-13cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	105x50x45 (LxWxH)	360g
mRs 785/660 Standard	**785**: 5-50mW **660**: 5-45mW	20, 35, 50µm	**785**: 500:1 **665**: 600:1	808-982nm	**785**: 300 - 3200cm-1 **660**: 2700-3700cm-1	**785**: 0.25nm/px, 6-9cm-1 / 7-10cm-1 / 9-13cm-1 **660**: 0.36nm/px, 12-15cm-1 / 13-17cm-1 / 15-18cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	105x50x45 (LxWxH)	360g

OEM solutions

Name	Laser power on sample	Spectral slit sizes	Signal-to-noise ratio*	Spectral Range	Raman shift	Spectral resolution	Grating	Physical dimensions	Weight
mRs OEM F **	according to base model	20, 35, 50µm	according to base model	according to base model	according to base model	according to base model	1500 l/mm	50x20x12 (LxWxH)	250g
mRs OEM spectrograph 660	no laser	20, 35, 50µm	N/A	according to base model	270 - 3700cm-1	0.36nm/px, 9-13cm-1 / 11-15cm-1 / 13-17cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	50x20x12 (LxWxH)	30g
mRs OEM spectrograph 785	no laser	20, 35, 50µm	N/A	according to base model	300 - 3200cm-1	0.25nm/px, 6-9cm-1 / 7-10cm-1 / 9-13cm-1 (for slit sizes 20/35/50µm)	1500 l/mm	50x20x12 (LxWxH)	30g

mRs Operator body

Name	Laser power on sample	Spectral slit sizes	Signal-to-noise ratio*	Spectral Range	Raman shift	Spectral resolution	Grating	Physical dimensions	Weight
mRs 660 Operator	5-50mW	35µm	500:1	679 - 882nm	250 - 3700cm-1	11-15cm-1	1500 l/mm	105x50x45 (LxWxH)	360g
mRs 785 Operator	10-50mW	35µm	1000:1	808-982nm	300 - 3200cm-1	7-10cm-1	1500 l/mm	105x50x45 (LxWxH)	360g

*Determined as peak signal-to-noise ratio of polystyrene spectrum at maximal laser power, integration time 0.3s, number of repetitions 10
** Full set with ANY laser and electronics